

Pear Shaped Connecting links, C-753-G



MADE IN THE USA

- Drop-Forged Heat-Treated Carbon Steel
- Galvanized to Meet ASTM A-153 Specifications
- 4 to 1 Design Factor
- For Proper Closure, Peen the Prongs to Fill the Hole of the Mating Half as Much as Possible
- Make Sure the Connecting Link Used is the Same Size as the Components Being Joined.
- Any Assembly Made Using Connecting Links Should be Rated at the Working Load Limit of the Weakest Component.
- The Working Load Limit of Connecting Links is Based on a Straight Line Pull. Any Side or Shock Loading Will Significantly Reduce the Actual Working Load Limit.
- NEVER Re-Use a Connecting Link
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Working Load Limit	B Dim.	C Dim.	D Dim.	E Dim.	Weight Each
3/8 in	**5205634**	074912	1850 lb	2-15/16 in	13/16 in	2 in	9/16 in	0.29 lb
1/2 in	**5205834**	074936	3300 lb	3-5/8 in	1 in	2-1/2 in	11/16 in	0.52 lb
5/8 in	**5206035**	074950	5000 lb	4-1/4 in	1-1/8 in	2-3/4 in	13/16 in	0.91 lb
3/4 in	**5206235**	074974	7100 lb	4-7/8 in	1-1/4 in	3-1/8 in	1 in	1.30 lb
7/8 in	**5206435**	074998	9600 lb	5-11/16 in	1-1/2 in	3-11/16 in	1-1/4 in	2.20 lb

ISO 9001:2015 Since 2006