


Cam-Alloy Sling Hooks






- For Use with Grade 80/100 Chain Slings
- 4 to 1 Design Factor
- Meet or Exceed All Requirements of ASME B30.9 and B30.10
- 100% Proof Tested in Accordance with ASTM A952
- Additionally Hallmarked with “USA” and Date Code
- Made in the USA
- DO NOT EXCEED THE WORKING LOAD LIMIT

Chain Size	Cat. No.	UPC No.	Grade	Working Load Limit	Weight Each	Replacement Latch No.
9/32 in, 5/16 in	**5646415PL**	020418319167	100	5700 lb	1.61 lb	**7506495PL**
3/8 in	**5646615PL**	020418319181	100	8800 lb	3.31 lb	**7506695PL**
1/2 in	**5646815PL**	020418319204	100	15000 lb	6.52 lb	**7506895PL**
5/8 in	**5647015PL**	020418319228	100	22600 lb	11.05 lb	**7507095PL**
3/4 in	**5647215PL**	020418319235	100	35300 lb	15.100 lb	**7507295PL**

Chain Size	Cat. No.	D Dim.	Ed Dim.	Es Dim.	H Dim.	OAL	OAW	R Dim.	S Dim.	W Dim.
9/32 in, 5/16 in	**5646415PL**	1-11/32 in	3/4 in	15/32 in	1-1/2 in	6 in	3-25/32 in	4-11/32 in	1-11/32 in	7/8 in
3/8 in	**5646615PL**	1-9/16 in	13/16 in	19/32 in	2-1/8 in	7 in	4-23/32 in	5-3/32 in	1-21/32 in	1-5/16 in
1/2 in	**5646815PL**	2-3/32 in	1-1/8 in	3/4 in	2-7/16 in	8-25/32 in	5-31/32 in	6-7/32 in	1-15/16 in	1-7/16 in
5/8 in	**5647015PL**	2-19/32 in	1-5/16 in	7/8 in	2-13/16 in	10-3/4 in	7-1/8 in	7-23/32 in	2-7/16 in	1-3/4 in
3/4 in	**5647215PL**	3-3/32 in	1-1/2 in	1 in	3-1/8 in	12 in	8-17/32 in	8-9/32 in	2-21/32 in	2-3/32 in

Cam-Alloy Sling Hooks with Latches





- For Use with Grade 80/100 Chain Slings
- 4 to 1 Design Factor
- Meet or Exceed All Requirements of ASME B30.9 and B30.10
- 100% Proof Tested in Accordance with ASTM A952
- Additionally Hallmarked with “USA” and Date Code
- Integrated Latch Engages Tip of Hook
- Made in the USA
- DO NOT EXCEED THE WORKING LOAD LIMIT

Chain Size	Cat. No.	UPC No.	Grade	Working Load Limit	Weight Each	Replacement Latch No.
9/32 in, 5/16 in	**5646495PL**	020418319174	100	5700 lb	1.67 lb	7506495PL
3/8 in	**5646695PL**	020418319198	100	8800 lb	3.41 lb	7506695PL
1/2 in	**5646895PL**	020418319211	100	15000 lb	6.68 lb	7506895PL

Chain Size	Cat. No.	D Dim.	Ed Dim.	Es Dim.	H Dim.	OAL	OAW	R Dim.	T Dim.	W Dim.
9/32 in, 5/16 in	**5646495PL**	1-11/32 in	3/4 in	15/32 in	1-1/2 in	6 in	3-25/32 in	4-11/32 in	1-5/32 in	7/8 in
3/8 in	**5646695PL**	1-9/16 in	13/16 in	19/32 in	2-1/8 in	7 in	4-23/32 in	5-3/32 in	1-15/32 in	1-5/16 in
1/2 in	**5646895PL**	2-3/32 in	1-1/8 in	3/4 in	2-7/16 in	8-25/32 in	5-31/32 in	6-7/32 in	1-11/16 in	1-7/16 in