
## Cam-Alloy Grab Hooks







- For Use with Grade 80/100 Chain Slings
- 4 to 1 Design Factor
- Meet or Exceed All Requirements of ASME B30.9 and B30.10
- 100% Proof Tested in Accordance with ASTM A952
- Additionally Hallmarked with “USA” and Date Code
- Made in the USA
- Note: Use of Chain in a Grab Hook as a Shortening Application May Result in a 20% WLL Reduction
- DO NOT EXCEED THE WORKING LOAD LIMIT

| Chain Size | Cat. No. | UPC No. | Hook No. | Grade | Working Load Limit | D Dim. | Ed Dim. | Es Dim. | OAL | OAW | R Dim. | T Dim. | W Dim. | Weight Each | Shelf Pack |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 9/32 in | **5624415** | 020418182303 | C-72 | 100 | 4300 lb | 0.81 in | 0.56 in | 0.37 in | 3.69 in | 1.87 in | 2.50 in | 0.37 in | 0.59 in | 0.60 lb | 50 |
| 3/8 in | **5624615** | 020418182310 | C-73 | 100 | 8800 lb | 1.16 in | 0.75 in | 0.44 in | 4.00 in | 2.56 in | 2.41 in | 0.50 in | 0.66 in | 0.90 lb | 30 |
| 1/2 in | **5624815** | 020418182327 | C-75 | 100 | 15000 lb | 1.44 in | 1.12 in | 0.56 in | 5.40 in | 3.50 in | 3.40 in | 0.66 in | 0.88 in | 2.80 lb | 20 |
| 5/8 in | **T5625015** | 020418182334 | C-76 | 100 | 22600 lb | 1.75 in | 1.22 in | 0.69 in | 6.66 in | 4.25 in | 4.22 in | 0.78 in | 1.12 in | 3.70 lb | - |
| 3/4 in | **5625215** | 020418182341 | C-77 | 100 | 35300 lb | 2.12 in | 1.44 in | 1.00 in | 8.28 in | 5.18 in | 5.15 in | 0.94 in | 1.38 in | 7.50 lb | - |
| 7/8 in | **T5625415** | 020418152979 | C-78 | 100 | 42700 lb | 2.44 in | 1.75 in | 1.00 in | 10.44 in | 5.68 in | 7.00 in | 1.06 in | 1.62 in | 11.20 lb | - |

## Self-Locking Eye Hooks





- Meet or Exceed All Requirements of ASME B30.9 and B30.10
- Fatigue and 100% Proof Tested in Accordance with ASTM A952
- Additionally Hallmarked with “USA” and Date Code
- Meets the Intent of OSHA Regulation 1926.550(g)(4)(iv)(b)
- Latch Closes Automatically Under Load
- Eye Style is Designed to Accommodate Heavy Duty Wire Rope Thimbles
- Stamped with Recommended Wire Rope Size
- Working Load Limit Rating of 5 to 1 to Meet Design Requirements of Wire Rope Slings
- Made in the USA
- DO NOT EXCEED THE WORKING LOAD LIMIT

| Chain Size | Cat. No. | UPC No. | Working Load Limit 4 to 1 | For Wire Rope Size | Working Load Limit 5 to 1 | Weight Each | Shelf Pack |
|---|---|---|---|---|---|---|---|
| 9/32 in | **5648495** | 020418193262 | 4300 lb | 7/16 in | 3800 lb | 2.25 lb | - |
| 3/8 in | **5648695** | 020418193279 | 8800 lb | 1/2 in | 7000 lb | 4.00 lb | - |
| 1/2 in | **5648895** | 020418193286 | 15000 lb | 5/8 in | 12000 lb | 8.65 lb | 1 |
| 5/8 in | **5649095** | 020418193293 | 22600 lb | 7/8 in | 18000 lb | 13.80 lb | 1 |

| Chain Size | Cat. No. | A Dim. | B Dim. | C Dim. | D Dim. | E Dim. | F Dim. | G Dim. | H Dim. | J Dim. | R Dim. |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 9/32 in | **5648495** | 1.875 in | 1.00 in | 0.938 in | 1.02 in | 3.594 in | 1.625 in | 0.438 in | 0.875 in | 1.25 in | 5.468 in |
| 3/8 in | **5648695** | 2.375 in | 1.375 in | 1.125 in | 1.250 in | 4.312 in | 1.875 in | 0.578 in | 1.063 in | 1.50 in | 6.50 in |
| 1/2 in | **5648895** | 3.188 in | 1.688 in | 1.312 in | 1.796 in | 5.404 in | 2.250 in | 0.688 in | 1.281 in | 1.75 in | 8.75 in |
| 5/8 in | **5649095** | 3.50 in | 2.00 in | 1.50 in | 2.169 in | 6.50 in | 2.375 in | 0.75 in | 1.50 in | 2.00 in | 10.00 in |