



## Dock Fender Chain - Drums

- High Tensile Chain Holds Thick Rubber Fenders to Dock Sides
- Hot Dipped Galvanized Finish
- Proof Tested
- Hallmarking: “C-DF”
- Packaged in Drums, Order Unit is “Feet”
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT





| Trade Size | Cat. No. | UPC No. | Material Diameter | Inside Length | Inside Width | Working Load Limit | Feet Per Pkg | Weight Per Pkg |
|---|---|---|---|---|---|---|---|---|
| 5/8 in | **T0516531*** | **020418181887** | 0.66 in | 3.75 in | 0.90 in | 12500 lb | 150 ft | 480 lb |

** Item is Made to Order*

## Beacon Fishing Chain

- Standard Material: Heat Treated Carbon Steel
- Standard Finish: Bright (Brt)
- Proof Tested
- Hallmarking: “CB” and “USA”
- Uses: Designed to Accommodate All Types of Chain Needs in the Trawling and Marine Industry
- Packaged in Drums, Order Unit is “Feet”
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



| Trade Size | Cat. No. | UPC No. | Material Diameter | Inside Length | Inside Width | Working Load Limit | Feet Per Pkg | Links Per Ft | Weight Per Pkg |
|---|---|---|---|---|---|---|---|---|---|
| 3/8 in | **T0520612** | **020418064302** | 0.39 in | 1.58 in | 0.59 in | 6600 lb | 200 ft | 7.6 | 268 lb |
| 1/2 in | **T0520812** | **020418064319** | 0.51 in | 2.05 in | 0.83 in | 11300 lb | 200 ft | 5.9 | 460 lb |
| 5/8 in | **T0521012** | **020418064326** | 0.63 in | 2.52 in | 0.94 in | 15800 lb | 200 ft | 4.8 | 680 lb |

## Grade 80, Cam-Alloy Chain

- Specifically Recommended for Overhead Lifting Applications
- Standard Material: Alloy Steel, Heat Treated
- Standard Finish: Bright
- Hallmarking: “C8”, “USA” and Traceability Code
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is “Feet”
- Made in the USA
- DO NOT EXCEED THE WORKING LOAD LIMIT



| Trade Size | Cat. No. | UPC No. | Material Diameter | Inside Length | Inside Width | Working Load Limit | Feet Per Pkg | Links Per Ft | Weight Per Pkg |
|---|---|---|---|---|---|---|---|---|---|
| 5/16 in | **T0400512** | **020418063367** | 0.32 in | 0.94 in | 0.46 in | 4500 lb | 500 ft | 12.8 | 460 lb |
| 1 in | **T0401612** | **020418063510** | 1.00 in | 3.18 in | 1.40 in | 47700 lb | 100 ft | 3.8 | 940 lb |
| 1-1/4 in | **T0402012** | **020418063534** | 1.25 in | 3.80 in | 1.75 in | 72300 lb | 60 ft | 3.5 | 915 lb |