


- Engineered flat is an oversized master link designed for use in 1- and 2-leg sling configurations.
- Compatible with CL, CLD, CG, and CGD components for flexible application in lifting assemblies.
- Clearly marked with the product type (M for single-type master link), size designation, and H32 (Gunnebo Industries manufacturing ID) verified by third-party audit from BG in Germany.
- Additional markings include a traceability code and the country of origin to ensure full traceability and identification.
- Meets EN 1677:2008 (WLL +25%), ASTM A952/A952M-02, AS 3775:2014, and AS 3776:2015 standards.
- 5:1 Design Factor

Grade 100 Welded Oversized Master Link MFX

Oversized, for 1- and 2-leg slings. Designed for use with CL, CLD, CG and CGD.

Stock No.	Code	WLL (t)	Proof Load (t)	For Grade 100 Chain Size (mm)		Dimensions (mm)				Weight (kg)
				For chain 1-leg	For chain 2-leg	L	E	D	Flat Thickness	
Z100923	MFX-108-10	5.4	5.4	10	8	340	180	22	8	3.7
Z100921	MFX-1310-10	8.2	8.2	13	10	340	180	28	10	4.6
Z100924	MFX-1613-10	13.6	13.6	16	13	340	180	32	13	7.0
Z100922	MFX-2016-10	20.6	20.6	20	16	340	180	40	16	9.7

5:1 Design Factor.



Master Link MF HDG with Engineered Flat

Stock No.	Code	WLL (t)		Dimensions (mm)				Weight (kg)
		EN1677-4	A-952/A952M	L	E	D	Flat Thickness	
BG14489	MF-86-8 HDG	2.0	2.5	120	60	13	6	0.36
BG14482	MF-108-8 HDG	3.2	4.0	140	80	17	8	0.76
BG14483	MF-1310-8 HDG	5.4	6.8	160	95	22	10	1.5
BG14484	MF-1613-8 HDG	8.2	10.3	275	145	28	13	3.9

5:1 Design Factor.

© 2025 Kito Crosby. All Rights Reserved.