VCGH-G

VIP-boltable attachment block.

RUD RFID CONNECT IT



PRODUCT FEATURES

- Large WLL range 10 t, 16 t–20 t.
- For combination with all conventional lifting means without additional connecting elements.
- ICE-Bolt made from patented steel. Safe deep temperature usage; improved toughness meaning higher bending strength and lower wear occurrence.
- Innovative wear markings for easy determination of wear.
- Robust forged safety latch.



✓ Corresponds with the test criteria of BG/DGUV “GS-HM 36”.

- As a lifting point on trusses and beams.
- For ropes and round slings.
- For lifting means with eye or oval ring.

p. 102–103

VCGH-G


Metric thread.

VABH-G – VIP-BOLTABLE ATTACHMENT BLOCK – METRIC.


Type	WLL [t]	Weight (kg/unit)	T [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	L [mm]	M	Tightening torque [Nm]	Ref. No.
VCGH-G-16	10	8.49	49	15	141	200	220	170	48	120	150	69	35	4 × M24	800	7984048
VCGH-G-20	16	18	69	20	187	272	288	210	63	150	2 × 110	87	30	6 × M24	800	7984311
VCGH-G-22	20	18.9	74	20	196	276	292	240	63	150	2 × 110	92	30	6 × M24	950	7984313

Subject to technical changes!


VCGH-G-16




VCGH-G-16



VCGH-G-20 / -22



VCGH-G-20 / -22



CÔNG TY CỔ PHẦN PHÁT TRIỂN KINH TẾ ĐÔNG NAM Á
ASEAN DEVELOPMENT JOINT STOCK COMPANY
ASEAN JSC VN
ISO 9001:2015
Since 2006