Clevis Master Links


TWN 1819

The grade 100 clevis master links TWN 1819 are predominantely used to assemble basket slings for bundling of loads. The manufacturing and testing requirements are based on the DIN EN 1677-1, under consideration of grade 100 load capacities.

SAFETY 4 : 1 | 100 %



Trade Size	Article-No.	Working Load Limit [t]	Dimensions [mm]							Weight app. [kgs]
			a	b	c	e	f	g	h	
13-10	F31025	6,70	189	102	32	142,5	60	110	22	1,11



Connectors

XL-LOK Connecting Links


TWN 1820

The grade 100 XL-LOK connecting links TWN 1820 are used to connect lifting chains with sling components to assemble chain slings and lashing chains. The manufacturing and testing requirements are based on DIN EN 1677-1, under consideration of grade 100 load capacities.

SAFETY 4 : 1 | DGUV ZERT | 100 %



Trade Size	Article-No.	Working Load Limit [t]	Dimensions [mm]						Weight app. [kgs]
			a	b	c	e	f	g	
6-10	F30807	1,40	61	12	38,5	45	8	14	0,07
7-10 NEW	F308090	1,90	71	14	47	50,5	9	16	0,14
8-10	F30817	2,50	85	16	55	62	10	19	0,20
10-10	F30827	4,00	97	18	66,5	72	13	24	0,35
13-10	F30837	6,70	125	23	82,5	87	17	28	0,74
16-10	F30847	10,00	146	31,5	109	105	21	34	1,20
20-10 NEW	F308570	16,00	178,5	37	143,5	127,5	25	45	2,80
22-10 NEW	F308670	19,00	196,5	40,5	150,5	140,5	27,5	45	3,50
26-10 NEW	F308770	26,50	232	47,5	178	166	33	56	5,80
32-10 NEW	F308870	40,00	285,5	58,5	220,5	204	40	70	10,9



CÔNG TY CỔ PHẦN PHÁT TRIỂN KINH TẾ ĐẠI DƯƠNG
ASEAN JSC.VN
ASEAN DEVELOPMENT JOINT STOCK COMPANY
ISO 9001:2015