
TWN 0855






Eye Sling Hooks

The grade 80 eye sling hooks TWN 0855 are used to assemble chain slings. The lifting chains are assembled by using connecting links, e.g. THI-LOK®s TWN 1320. The manufacturing and testing requirements comply with the DIN EN 1677-2.

Trade Size	Article-No.	Working Load Limit [t]	Dimensions [mm]						Weight app. [kgs]
			e	d_1	g	h	c	d_2	
36-8	Z04079	40,00	388	72	109	103	78	44,5	31,50
40-8	Z04083	50,00	442	84	124	116	89	50,5	46,00
45-8	Z04080	63,00	494	90	138	130	99	56	63,00
50-8	Z04081	80,00	610	102	155	145	110	63	80,00

TWN 0855/1






Eye Sling Hook with Safety Latch

The grade 80 eye sling hooks TWN 0855/1 are used to assemble chain slings. The lifting chains are assembled by using connecting links, e.g. THI-LOK®s TWN 1320. The safety latch prevents unintentional detachment from the load. The sling hooks comply with the DIN EN 1677-2.

Trade Size	Article-No.	Working Load Limit [t]	Dimensions [mm]						Weight app. [kgs]
			e	d_1	g	h	c	d_2	
36-8	Z06159	40,00	388	72	90	103	78	44,5	32,30
40-8	Z06160	50,00	442	84	103	116	89	50,5	47,00
45-8	Z06161	63,00	494	90	114	130	99	56	64,40
50-8	Z06162	80,00	610	102	131	145	110	63	81,90

TWN 0856





Eye Foundry Hooks

The grade 80 eye foundry hooks TWN 0856 are used to assemble chain slings, primarily for foundries. The associated lifting chains are assembled by using connecting links, e.g. THI-LOK®s TWN 1320. The manufacturing and testing requirements comply with the DIN EN 1677-1.

Trade Size		Article-No.	Working Load Limit [t]	Dimensions [mm]							Weight app. [kgs]
				e	d_1	g	h	c	d_2	f	
6-8	NEW	F32354	1,12	108	21[1)]	50	24	20	12	-	0,44
7/8-8	NEW	F32364	2,00	135	28[1)]	66	33	26	14	-	0,97
10-8	NEW	F32374	3,15	161	32[1)]	76	35	32	18	-	1,56
13-8	NEW	F32384	5,30	196	42[1)]	89	42	38	21	-	2,96
16-8	NEW	F32394	8,00	229	54[1)]	102	48	45	23	-	4,71
18/20-8	NEW	F32404	12,50	259	59	114	63	59	27,0	70	7,95
22-8	NEW	F32414	15,00	288	65	127	70	65	30	78	10,88
26-8	NEW	F32424	21,20	329	76	136	81	75	35	89	16,49
32-8	NEW	F32444	31,50	358	85	152	97	83	42	100	26,20

[1)] *With circular eyelet*