


- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 2 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.

Each product is assigned a unique Serial Number, enabling full Traceability and linking to an ESPR-compliant Digital Product Passport (DPP).

G-100 Swivel Hook

Item NO.	Hook Feature Code	For Grade 100 Chain	Working Load Limit	Dimensions (mm)												N.W.
		mm	tonnes*	A	B	C	D	G	H	K	L	P	P1	T	kg
X-175-05	AA	5	1.0	32	23	25	12	78	19	123	154	26	22	16	0.6
X-175-06	BB	6	1.4	32	23	25	12	81	23	131	165	24	19	17	0.7
X-175-07	CC	7.8	2.5	36	29	26	13	90	27	145	184	24	20	22	1.0
X-175-10	DD	10	4.0	41	35	29	16	102	29	172	217	28	25	24	1.5
X-175-13	EE	13	6.7	46	44	38	21	122	38	218	277	35	31	31	3.2
X-175-16	FF	16	10.0	61	50	49	23	160	48	261	332	43	39	35	5.7
X-175-20	GG	18-20	16.0	74	82	62	25	196	56	327	410	61	57	47	9.5
X-175-22	HH	22	19.0	97	96	65	33	221	64	372	471	72	62	56	16.5
X-175-26	JJ	26	26.5	123	116	71	51	277	76	469	599	86	81	68	33.4
X-175-32	KK	32	40.0	123	116	87	51	353	93	503	651	89	83	76	45.9

* Design factor 4:1 proof tested and certified.

WARNING
NEVER EXCEED PUBLISHED WORKING LOAD LIMIT

Copyright © 2026
YOKE Industrial Corp.
All Rights Reserved.