






- ROV: Remotely Operated Vehicle.
- Forged alloy steel, quenched and tempered.
- Designed specifically for ROV application.
- Individually stamped with the Working Load Limit.
- Shackle Bows are painted yellow to ensure ease of sight in water.

Each product is assigned a unique Serial Number, enabling full Traceability and linking to an ESPR-compliant Digital Product Passport (DPP).



ROV Anchor Shackle

with Safety Pin

Item No.	Nominal Size	Working Load Limit	Dimensions (mm)									N.W.
	inch	tonnes*	A	E	H	O	P	Q	S	T	W	kg
8-911-22	7/8	6.5	86	58	148	50	63	30	19	10	38	1.8
8-911-26	1	8.5	96	69	166	50	65	30	20	10	44	2.5
8-911-28	1 1/8	9.5	111	74	190	70	88	35	21	12	46	3.6
8-911-32	1 1/4	12.0	121	84	210	70	88	35	25	12	54	4.8
8-911-36	1 3/8	13.5	134	92	232	75	96	40	27	15	59	6.8
8-911-38	1 1/2	17.0	146	99	254	75	98	40	27	15	60	8.3
8-911-45	1 3/4	25.0	178	127	313	90	114	50	30	20	73	16.6
8-911-50	2	35.0	197	146	347	106	132	60	30	20	83	23.4

* Minimum Ultimate Load is 5 times the Working Load Limit.
Maximum Proof Load is 2 times the Working Load Limit.

Copyright © 2026
YOKE Industrial Corp.
All Rights Reserved.

WARNING
NEVER EXCEED PUBLISHED WORKING LOAD LIMIT