Thrust Bearing Swivels



- YOKE's Thrust Roller Bearing Swivels are manufactured using the highest grade of material available.
- YOKE's Thrust Roller Bearing Swivels are designed with a safety factor of 5:1.
- YOKE's Thrust Roller Bearing Swivels are available in sizes from 3 to 10 tons.
- YOKE's Thrust Roller Bearing Swivels are available for wire line 13mm to 22mm.
- YOKE's Thrust Roller Bearing Swivels are coated for corrosion resistance and longer service life.
- YOKE's Thrust Roller Bearing Swivels are manufactured with grease fitting for superior performance.
- YOKE's Thrust Roller Bearing Swivels are designed for low starting torque and high rotation speed.
- All parts of YOKE's Thrust Roller Bearing Swivels are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times the working load limit.
- All parts of YOKE's Thrust Roller Bearing Swivels come with a batch number for quality certification and traceability.

8-322 Jaw & Safe Locking Hook

Thrust Roller Bearing Swivels

Item No.	Nominal Size	Working Load Limit	Dimensions (mm)													N.W.
	mm	tonnes*	A	B	C	D	E	G	H	K	L	P	Q	R	S	kg
8-322-03	13	3.0	22.5	70	25.5	19.0	41.5	156	33.5	244	301	47	49	31	27	4.1
8-322-05	16	5.0	25.0	76	29.0	22.0	57.0	174	41.0	304	372	80	64	39	34	7.5
8-322-085	19	8.5	40.0	102	35.0	25.4	72.0	213	54.0	376	458	113	78	47	39	13.2
8-322-10	22	10.0	4.04	114	44.0	38.0	86.0	251	89.0	468	568	132	92	56	54	23.0

* Minimum Ultimate Load is 6 times the Working Load Limit.
  Maximun Proof Load is 2 times the Working Load Limit.
* Design factor 5:1
  Proof load is 2 times the WLL.

WARNING
NEVER EXCEED PUBLISHED WORKING LOAD LIMIT

Copyright © 2026
YOKE Industrial Corp.
All Rights Reserved.