


- YOKE Spelter Sockets are forged from special bar quality carbon steel with very finest hardness controlled.
- YOKE Spelter Sockets properly applied have an efficiency rating of 100% based on the catalog strength of wire rope.
- Socket size 6mm to 20mm use one groove, 22mm to 38mm use 2 grooves.
- Open Spelter sockets meet the performance requirements of Federal Specification RR-S-550E ,Type A.
- Galvanized finish or self colored.

In accordance with ASME B30.9, all assembly slings with poured spelter shall be proof loaded.

Open Spelter Wire Rope Socket

Item No.		Rope Dia.	Structural Strand Dia.	Ultimate Load	Before Swage Dimensions (mm)										N.W.
S.C.*	Galvanized	mm	mm	tonnes	A	C	D	D1	d	H	K	L	T	W	kg
8-733-06	8-733-06G	6 - 7	-	8	33	9	18	17	11	57	40	115	39	23	0.7
8-733-10	8-733-10G	8 - 10	-	12	38	11	21	20	13	57	45	123	44	21	0.9
8-733-13	8-733-13G	11 - 13	-	20	48	13	25	25	15	63	54	142	50	25	1.6
8-733-16	8-733-16G	14 - 16	13	27	58	14	29	30	18	76	64	172	57	32	2.2
8-733-19	8-733-19G	18 - 20	14 - 16	43	67	16	32	35	22	92	76	202	67	38	3.4
8-733-22	8-733-22G	22 - 23	18 - 20	55	80	20	38	41	24	102	89	235	85	45	5.4
8-733-26	8-733-26G	24 - 26	22 - 23	76	96	23	44	51	29	114	102	268	95	52	8.5
8-733-28	8-733-28G	28 - 30	24 - 25	92	105	25	51	56	32	127	117	300	105	57	11.6
8-733-36	8-733-36G	32 - 35	26 - 28	136	121	29	57	62	38	140	127	335	120	64	16.0
8-733-38	8-733-38G	36 - 38	30 - 32	170	137	30	70	70	41	152	152	384	133	76	24.0

* S.C. = Self Colored.

Copyright © 2026
YOKE Industrial Corp.
All Rights Reserved.

WARNING
NEVER EXCEED PUBLISHED WORKING LOAD LIMIT