



- Manufactured from forged alloy steel, quenched and tempered.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts are traceable to Test Certification.
- All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.
- WLL forged onto each product for quick and easy identification.
- Lugs designed to assist the welding process.





Excavator Hook

Metric (8-083)

Item No.	Working Load Limit	Dimensions (mm)								N.W.
	tonnes	F	H	L	P	T	W	HV	a	kg
8-083-0075	0.75	19	20	56	18	13	82	5	3	0.3
8-083-01	1.00	25	27	72	20	17	95	6	4	0.6
8-083-02	2.00	30	30	86	27	20	114	8	5	0.9
8-083-03	3.00	35	32	105	29	23	132	10	6	1.4
8-083-04	4.00	42	38	112	30	29	140	11	7	1.9
8-083-05	5.00	45	47	131	32	30	165	12	8	2.9
8-083-08	8.00	50	51	133	34	40	172	13	9	3.5
8-083-10	10.00	55	57	170	51	43	220	14	10	6.3
8-083-15	15.00	60	67	191	53	50	240	15	12	8.8

* Design Factor 5:1

Copyright © 2026
YOKE Industrial Corp.
All Rights Reserved.

WARNING
NEVER EXCEED PUBLISHED WORKING LOAD LIMIT