# CLOSED SPELTER SOCKET

| | | |
|---|---|---|
| Material | : | Cast steel |
| Working Load Limit | : | 20% of the MBL |
| Finish | : | Painted or galvanised (< Type No. 201 standard galvanised) |
| Temperature Range | : | -40°F up to 392°F |
| Standard Certification | : | Certificate of Conformity<br>3.1 material certificate EN 10204 |

*TYPE APPROVED PRODUCT*


DNV

**Sockets are Type Approved by DNV according DNV ST-0378**

These sockets include our non-rotating system (NRS-system) which prevents the tamp from turning or slipping out of the cone and guarantees a high performance connection.

**Non-standard sizes or custom products available on request.**






| NR. | Rope Ø | Article number | | MBL | A | B | C | ØD | E | F | G | Weight |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | inch | painted RAL 5013 blue | galvanised | USt | inch | | | | | | | lbs |
| 290 | ¼ | - | CSS290G | 8,8 | 2 | 1 13/16 | 7/16 | 5/16 | 13/16 | 1 7/16 | ½ | 0,7 |
| 292 | 5/16 - ⅜ | - | CSS292G | 13,2 | 2 5/16 | 2 ⅛ | 9/16 | 7/16 | 29/32 | 1 23/32 | ⅝ | 0,9 |
| 294 | 7/16 - ½ | - | CSS294G | 22,0 | 2 ½ | 2 ⅜ | 23/32 | 9/16 | 1 ⅛ | 2 | ⅞ | 1,8 |
| 296 | 9/16 - ⅝ | - | CSS296G | 33,1 | 3 | 2 9/16 | 13/16 | 23/32 | 1 ⅜ | 2 ⅝ | 1 | 3,1 |
| 298 | ¾ | - | CSS298G | 44,1 | 3 ½ | 3 | 1 | 27/32 | 1 1/16 | 3 | 1 ¼ | 4,6 |
| 201 | ⅞ | CSS201P | CSS201G | 66,1 | 4 | 3 ½ | 1 5/16 | 29/32 | 1 ⅞ | 3 ⅝ | 1 ½ | 8,8 |
| 204 | 1 | CSS204P | CSS204G | 82,7 | 4 ½ | 4 ⅛ | 1 7/16 | 1 ⅛ | 2 ¼ | 4 3/16 | 1 25/32 | 13,2 |
| 207 | 1 ⅛ | CSS207P | CSS207G | 110,2 | 5 | 4 13/32 | 1 ½ | 1 ¼ | 2 ½ | 4 ½ | 2 | 16,5 |
| 212 | 1 ¼ - 1 ⅜ | CSS212P | CSS212G | 137,8 | 5 ½ | 5 1/16 | 1 ¾ | 1 ½ | 2 ¾ | 5 | 2 5/16 | 24,3 |
| 215 | 1 ½ | CSS215P | CSS215G | 165,3 | 6 | 6 ⅛ | 2 | 1 ⅝ | 3 ⅛ | 5 7/16 | 2 ½ | 30,9 |
| 217 | 1 ⅝ | CSS217P | CSS217G | 198,4 | 6 ½ | 6 ¾ | 2 ⅛ | 1 ¾ | 3 ¼ | 5 ¾ | 2 ¾ | 38,6 |
| 219 | 1 ¾ - 1 ⅞ | CSS219P | CSS219G | 253,5 | 7 ½ | 7 13/16 | 2 7/32 | 2 | 3 ½ | 6 ¾ | 3 | 60,6 |
| 222 | 2 - 2 ⅛ | CSS222P | CSS222G | 308,6 | 8 ½ | 8 13/16 | 2 15/32 | 2 ¼ | 3 ⅞ | 7 1/16 | 3 5/16 | 88,2 |
| 224 | 2 ¼ - 2 ⅜ | CSS224P | CSS224G | 413,4 | 9 | 9 23/32 | 2 ⅞ | 2 9/16 | 4 ⅜ | 8 ½ | 3 23/32 | 114,6 |
| 226 | 2 ½ - 2 ⅝ | CSS226P | CSS226G | 468,5 | 9 ¾ | 10 ⅝ | 3 5/32 | 2 ⅞ | 5 ½ | 9 ½ | 4 | 138,9 |
| 227 | 2 ¾ - 2 ⅞ | CSS227P | CSS227G | 551,2 | 11 | 11 ¼ | 3 ⅛ | 3 ⅛ | 6 ¼ | 10 ¾ | 4 ⅞ | 195,1 |
| 228 | 3 - 3 ⅛ | CSS228P | CSS228G | 661,4 | 12 | 11 ¾ | 3 ¼ | 3 7/16 | 6 ¾ | 11 ½ | 5 ¼ | 244,7 |
| 229 | 3 ¼ - 3 ⅜ | CSS229P | CSS229G | 771,6 | 13 | 12 ¼ | 4 | 3 ⅝ | 7 ¼ | 12 ¼ | 5 ¾ | 315,3 |
| 230 | 3 ½ - 3 ⅝ | CSS230P | CSS230G | 826,7 | 14 | 13 | 4 | 3 29/32 | 7 ¾ | 13 | 6 ¼ | 366,0 |
| 231 | 3 ¾ - 4 | CSS231P | CSS231G | 1047,2 | 15 | 14 | 4 ¼ | 4 ¼ | 8 ½ | 14 ¼ | 7 | 478,4 |
| 233 | 4 ½ | CSS233P | CSS233G | 1322,8 | 18 ⅛ | 16 ¾ | 4 23/32 | 4 29/32 | 9 ¼ | 15 29/32 | 7 ½ | 745,2 |
| 240 | 5 | CSS240P | CSS240G | 1543,2 | 19 1/16 | 18 23/32 | 5 ½ | 5 7/16 | 10 ⅝ | 20 5/16 | 8 ¼ | 1276,5 |
| 250 | 5 ½ - 6 | CSS250P | CSS250G | 2204,6 | 22 27/32 | 21 1/16 | 5 29/32 | 6 5/16 | 11 13/16 | 20 ⅛ | 9 27/32 | 1441,8 |
| 260 | 6 ½ | CSS260P | CSS260G | 2755,8 | 26 19/32 | 23 ⅝ | 6 29/32 | 6 29/32 | 12 13/16 | 23 ⅝ | 11 27/32 | 2343,5 |