
Eye type [fittings components]

- When assembling the fittings components, assemble them correctly according to the separate “Assembly Manual”.
- The specifications of eye-type fittings components are shown in the tables below. For the link chain specification table, refer to page 6.
- In addition to using the eye-type components by assembling them as Kito chain sling 100 products, they can also be used for many other purposes.
- Each fitting is not provided with a Hi-coupling HC. This should be ordered at the same time when placing the order for the fitting.


Master link
HMM



Working Load Limits (t)	Chain diamete (mm)			Code	Dimensions (mm)				Mass (weight) (kg)
	S	D	T,Q		p	a	d	t	
1.1	ø6	—	—	HMM0706	110	60	13.5	12	0.34
1.7	ø7	ø6							
2.4	ø8	ø7	ø6	HMM0807			16	13.5	0.53
3.2	ø10	ø8	ø7	HMM1008	135	75	19	15.5	0.92
5.2	ø13	ø10	ø8	HMM1310	160	90	23	19.5	1.6
8.0	ø16	ø13	ø10	HMM1613	180	100	27	21.5	2.5
12.5	ø20	ø16	ø13	HMM2016	200	110	33	27.5	4.2
20.0	—	ø20	ø16	HMM2220	275	150	38	31.5	7.5


- The chain diameters S, D and TQ show the number of sling legs. S: single leg slings, D: double leg slings, TQ: triple and quadruple leg slings

Sling hook
HTL (HTL4)




Working Load Limits (t)	Chain diameter (mm)	Code	Dimensions (mm)							Mass (weight) (kg)
			p	a	b	n	m'	s	t	
1.1	ø6	HTL4060	100	23	11	45	26	24.5	18	0.49
1.5	ø7	HTL4080	120	27	13.5	50	31	30	21.8	0.84
2.0	ø8									
3.2	ø10	HTL4100	140	32.5	17	56	39	37.5	27.2	1.6
5.2	ø13	HTL4130	171	38	21.5	63	46	47.5	34.5	3.0
8.0	ø16	HTL4160	200	46	26.5	75	53	60	45	5.7
12.5	ø20	HTL4200	250	54	34	95	68	75	56	10.4

Self locking hook
HJJ




Working Load Limits (t)	Chain diameter (mm)	Code	Dimensions (mm)								Mass (weight) (kg)
			p	a	b	n	m	m'	s	t	
1.1	ø6	HJJ06	110	21	12	35	28	28	20.5	16	0.56
1.5	ø7	HJJ08	136	27	12	43.5	34	34	26	20	1.0
2.0	ø8										
3.2	ø10	HJJ10	168.5	34.5	15	56	45	45	30	24.5	1.7
5.2	ø13	HJJ13	205	40	20	69	51.5	51.5	40	34.5	3.4
8.0	ø16	HJJ16	251.5	50	27	80	60	60	50	36.5	6.4

Swivel hook
HJK



Working Load Limits (t)	Chain diameter (mm)	Code	Dimensions (mm)									Mass (weight) (kg)
			p	a	b	c	n	m	m'	s	t	
1.1	ø6	HJK06	160	35	13	32	35	28	28	20.5	16	0.84
1.5	ø7	HJK08	181	35	13	32	43.5	34	34	26	20	1.2
2.0	ø8											
3.2	ø10	HJK10	218.5	42	16	39	56	45	45	30	24.5	2.1
5.2	ø13	HJK13	267.5	50	20.5	45.5	69	51.5	51.5	40	34.5	4.2

Foundry hook
HSF



Working Load Limits (t)	Chain diameter (mm)	Code	Dimensions (mm)						Mass (weight) (kg)
			p	a	b	n	s	t	
1.1	ø6	HSF06	102	15	11	53	26	21.5	0.65
1.5	ø7	HSF08	123	18	13.5	63	31	26	1.2
2.0	ø8								
3.2	ø10	HSF10	149	22	16	77	36	32	2.1
5.2	ø13	HSF13	173.5	27	19	88	43	39	3.5
8.0	ø16	HSF16	205	32	24	100	50	45	5.6
12.5	ø20	HSF20	237	38	27	115	61	51	8.1

CÔNG TY CỔ PHẦN PHÁT TRIỂN KINH TẾ ĐÔNG NAM Á
ASEAN DEVELOPMENT JOINT STOCK COMPANY
ASEAN-SSC.VN
ISO 9001:2015
since 2006